
AIRENG PTY LTD PERFORMANCE BY DESIGN

BAYSWATER VICTORIA AUSTRALIA ACN 060 583 164 PHONE: (03) 9738 1999 FAX: (03) 9738 1766 E-MAIL: fans@aireng.com.au

HS450- HIGH EFFICIENCY HEATERS

HOT WATER & STEAM HEATERS

ARRANGEMENT 4 DIRECT DRIVE



MODEL No.	MOTOR RPM	HEATER COIL	OUTPUT BTU*	OUTPUT kJ*	WATER I/s	PIPE FITTING	AIR I/s	MASS kg.
HS450HW6	900	D	65,100	62	0.49	1" BSP	700	51
HS450HW4	1400	D	82,500	79	0.38	1" BSP	1435	51
HS450S6S	900	S	76,300	72	N/A	1.25" BSP	680	57
HS450S4S	1400	S	86,200	82	N/A	1.25" BSP	1400	57
HS450S6D	900	D	121,000	115	N/A	1.25" BSP	680	57
HS450S4D	1400	D	156,700	149	N/A	1.25" BSP	1400	57

S= Single Row D= Double Row, * Based on 85°C Hot Water Supply * Steam Pressure of 14kPa (≈2PSI)

ADVANTAGES OF USING AIRENG HS450 HEATERS: Low Operating Cost, Adjustable Louvres To Direct Hot Air Flow, High Heat Output, Quiet Operation, Robust Construction, Quality Product For Long Service Life, Low Maintenance, Modern Styling,

STANDARD HEATER INCLUDES: Casing (Grey Hammertone), Impeller, Class F IP55 Three Phase Motor, Louvre, Motor Mount & Heater Coil.

OPTIONS INCLUDE: H.D. Gal./Special Coating, Mounting Feet, Flexible Mounts, Safety Guards, Hazardous Location Applications, Single Phase Motors, Two Speed Motors, etc......

IMPELLERS / CASINGS ARE ALSO AVAILABLE IN: ALUMINIUM, STAINLESS STEEL, SPECIAL ALLOYS Form no. /masters/HS450.PUB